

アルミニウム板

A5052P

板厚 mm	幅×長さ mm	調質				板厚 mm	幅×長さ mm	調質			
		H32	H34	O	H112			H32	H34	O	H112
0.3	1,000 × 2,000		◎			6.0	1,250 × 2,500			◎	◎
0.4	1,000 × 2,000		◎				1,525 × 3,050		◎		◎
0.5	1,000 × 2,000	◎	◎	◎		7.0	1,000 × 2,000				◎
	1,250 × 2,500	◎	◎	◎			1,250 × 2,500				◎
0.6	1,000 × 2,000	◎	◎	◎			1,525 × 3,050				◎
0.8	1,000 × 2,000	◎	◎	◎		8.0	1,000 × 2,000				◎
	1,250 × 2,500	◎	◎				1,250 × 2,500				◎
1.0	1,000 × 2,000	◎	◎	◎			1,525 × 3,050			◎	◎
	1,250 × 2,500	◎	◎			10	1,000 × 2,000				◎
1.2	1,000 × 2,000	◎	◎	◎			1,250 × 2,500				◎
	1,250 × 2,500	◎	◎				1,525 × 3,050			◎	◎
1.5	1,000 × 2,000	◎	◎	◎		12	1,000 × 2,000				◎
	1,250 × 2,500	◎	◎				1,250 × 2,500			◎	◎
1,525 × 3,050		◎	◎				1,525 × 3,050			◎	◎
1.6	1,000 × 2,000	◎	◎	◎		15	1,000 × 2,000				◎
	1,250 × 2,500		◎	◎			1,250 × 2,500				◎
2.0	1,000 × 2,000	◎	◎	◎			1,525 × 3,050				◎
	1,250 × 2,500	◎	◎	◎		2,050 × 3,500				◎	
2.3	1,000 × 2,000		◎			16	1,000 × 2,000				◎
	1,000 × 2,000	◎	◎	◎			1,250 × 2,500				◎
2.5	1,250 × 2,500	◎	◎				1,525 × 3,050				◎
	1,525 × 3,050		◎			18	1,000 × 2,000				◎
3.0	1,000 × 2,000	◎	◎	◎			1,250 × 2,500				◎
	1,250 × 2,500	◎	◎	◎			1,525 × 3,050				◎
3.2	1,000 × 2,000		◎			20	1,000 × 2,000				◎
	1,000 × 2,000		◎				1,250 × 2,500			◎	◎
3.5	1,000 × 2,000		◎				1,525 × 3,050				◎
4.0	1,000 × 2,000	◎	◎	◎		22	1,000 × 2,000				◎
	1,250 × 2,500		◎				1,250 × 2,500			◎	◎
1,525 × 3,050		◎					1,525 × 3,050			◎	◎
4.5	1,000 × 2,000		◎			25	1,000 × 2,000				◎
5.0	1,000 × 2,000	◎	◎	◎			1,250 × 2,500				◎
	1,250 × 2,500		◎	◎			1,525 × 3,050				◎
6.0	1,000 × 2,000		◎		◎	2,050 × 3,500				◎	

アルミニウム板

A5052P

板厚 mm	幅×長さ mm	調 質				板厚 mm	幅×長さ mm	調 質			
		H32	H34	O	H112			H32	H34	O	H112
30	1,000 × 2,000				◎	75	1,525 × 3,050				◎
	1,250 × 2,500				◎	80	1,250 × 2,500				◎
	1,525 × 3,050				◎		1,525 × 3,050				◎
	2,050 × 3,500				◎	85	1,250 × 2,500				◎
35	1,000 × 2,000				◎		1,525 × 3,050				◎
	1,250 × 2,500				◎	90	1,250 × 2,500				◎
	1,525 × 3,050			◎	◎		1,525 × 3,050				◎
40	1,000 × 2,000				◎	95	1,250 × 2,500				◎
	1,250 × 2,500				◎		1,525 × 3,050				◎
	1,525 × 3,050				◎	100	1,250 × 2,500				◎
	2,050 × 3,500				◎		1,525 × 3,050				◎
45	1,000 × 2,000				◎	110	1,525 × 3,050				◎
	1,250 × 2,500				◎	120	1,525 × 3,050				◎
	1,525 × 3,050				◎		130	1,525 × 3,050			
50	1,000 × 2,000				◎	140	1,525 × 3,050				◎
	1,250 × 2,500				◎	150	1,525 × 3,050				◎
	1,525 × 3,050				◎		160	1,525 × 3,050			
55	1,000 × 2,000				◎	170	1,525 × 3,050				◎
	1,250 × 2,500				◎	180	1,525 × 3,050				◎
	1,525 × 3,050				◎		190	1,525 × 3,050			
60	1,000 × 2,000				◎	200	1,525 × 3,050				◎
	1,250 × 2,500				◎	230	1,250 × 3,050				◎
	1,525 × 3,050				◎		250	1,250 × 2,500			
65	1,250 × 2,500				◎	260	1,500 × 2,300				◎
	1,525 × 3,050				◎	290	1,500 × 2,000				◎
70	1,250 × 2,500				◎		300	1,500 × 2,000			
	1,525 × 3,050			◎	◎	320	1,500 × 1,500				◎
75	1,250 × 2,500				◎		350	1,500 × 1,500			

KN シリーズ 520

品名	板厚(mm)	幅(mm)	長(mm)	調 質	製造方法	保管 ビニール	切 断	切断方法	切断公差
KN520 (A5052 相当)	20 ~ 585	200 ~ 2,130	200 ~ 3,440	○	連続 鋳造品	なし	可	帯鋸	+ 5.0,-0
	20 ~ 680	200 ~ 1,890	200 ~ 3,430						
	20 ~ 390	200 ~ 2,500	200 ~ 4,000						
	20 ~ 490	200 ~ 2,500	200 ~ 3,500						

加工歪極小な合金です。真空容器低圧成型用金型材等に最適な合金です。