



アルミ合金押出型材




チャンネル(R無) A6063S-T5

t × A × B	長さ	t × A × B	長さ	t × A × B	長さ
1.5 × 10 × 10	4,000	2.4 × 30 × 30	4,000	4.0 × 80 × 40	4,000
1.5 × 15 × 15	4,000	2.4 × 35 × 20	4,000		
1.5 × 20 × 12	4,000			5.0 × 75 × 50	4,000
		2.5 × 20 × 20	4,000	5.0 × 100 × 50	4,000
1.6 × 10 × 10	4,000	2.5 × 50 × 25	4,000	5.0 × 100 × 50	4,000
		3.0 × 15 × 15	4,000	6.0 × 75 × 40	4,000
2.0 × 12 × 12	4,000	3.0 × 26 × 23	4,000	6.0 × 80 × 40	4,000
2.0 × 15 × 15	4,000	3.0 × 30 × 25	4,000	6.0 × 125 × 65	4,000
2.0 × 18 × 10	4,000	3.0 × 40 × 20	4,000		
2.0 × 20 × 20	4,000	3.0 × 50 × 25	4,000	8.0 × 150 × 75	4,000
2.0 × 22 × 12	4,000	3.0 × 60 × 30	4,000	8.0 × 150 × 75	5,000
2.0 × 25 × 25	4,000				
2.0 × 30 × 15	4,000	3.2 × 75 × 40	4,000		
2.0 × 35 × 20	4,000				
2.0 × 40 × 20	4,000	3.6 × 90 × 30	4,000		



チャンネル(R付) A6063S-T5

t × A × B	長さ	t × A × B	長さ	t × A × B	長さ
5 × 100 × 50	4,000	6 × 75 × 40	4,000	6/9 × 125 × 65	5,000
		6 × 80 × 40	4,000		
		6 × 125 × 65	4,000	8 × 150 × 75	4,000
		6 × 125 × 65	5,000	8 × 150 × 75	5,000



Cチャンネル A6063S-T5

t × A × B × C	長さ	t × A × B × C	長さ
3 × 70 × 23 × 10	4,000	3 × 100 × 25 × 20	4,000